



Cafe Azzurro C6 TECHNICAL SPECIFICATION

- Versions (all versions are available with tank or with water mains connection)
- Espresso N° of canisters 2 (ES), 3 (IN - FB)
- User interface Direct selections with large pushbuttons
- Pushbuttons Up to 8
- Communication protocol Executive - MDB - BDV Display
- Blue alphanumeric with 2 lines x 16 characters
- Voltage 230 V
- Frequency 50 Hz
- Boiler capacity 0,3 litres (Espresso) / 0,6 litres (Espresso)
- 3,8 litres (FB / IN)
- Maximum productivity (per hour continuous use)
- 60 selections (55cc) / 3,3 litres (Espresso)
- 128 selections (170cc) / 22 litres (FB)
- 288 selections (55cc) / 16 litres (IN)
- Liquid waste container 1,4 litres Solid waste container
- Approx. 25/30 doses (coffee grounds)
- Dimensions (h x w x d)
- 50 x 33 x 52 cm (Machine)
- 50 x 51 x 52 cm (Machine with external tank)
- Weight 27 kg approx. Height of base cabinet
- 83 cm
- Weight 27 kg approx. Weight 27 kg approx.

Cafe Azzurro C6



Cafe Azzurro Limited, Century House, 2 Century Park, Starley Way, Bickenhill, West Midlands, B37 7HF
tel: 0870 751 7519 fax: 0870 751 7716 email: sales@cafe-azzurro.com web: www.cafe-azzurro.com